



ACRYLITE[®] acrylic sheet The Clear Choice for Conservation Glazing

ACRYLITE* acrylic sheet offers you and your customer numerous advantages over glass which is why it is the clear choice for many museums and galleries. It offers beautiful clarity without heaviness or breakability. And it provides museum-quality protection essential in preserving art and artifacts.

ACRYLITE[®] sheet provides what glass can't deliver:

- 10 20 times more resistant to impact
- Safer alternative at half the weight
- · Easier to handle and install
- · More economical to ship
- Exceptional optical clarity

Guaranteed Quality

ACRYLITE[®] FF3 sheet is the premier acrylic framing grade guaranteed defect free or your money back. It is exceptional general purpose glazing for cherished memorabilia, photographs and prints as well as valued artwork.

Protection from UV Light (OP3)

UV filtering ACRYLITE[®] sheet provides the highest protection from damaging ultraviolet light, protecting paper-borne artwork, prints and documents from fading, yellowing and brittling. These conservation grades are available in cell cast or extruded sheet and provide exceptional showcasing and enduring protection.

Protection from Glare (P99)

ACRYLITE® non-glare sheet is designed to minimize glare and reflection and maximize the unhindered viewing of framed artwork and prints. The matte finish shows off the art from almost any angle under typical lighting conditions.

Protection from Abrasion and Chemicals

ACRYLITE® Optical mar resistant sheet has an abrasion and chemical resistant coating on one or both surfaces. This added protection reduces the risk of scratching or damage when handling. Abrasion resistance and UV filtering properties can be combined for maximum conservation protection. These products can be easily cleaned with common household cleaners such as Windex®.



ACRYLITE[®] acrylic sheet The Clear Choice for Conservation Glazing

Mix and Match Performance

ACRYLITE[®] sheet is versatile and provides a variety of benefits to satisfy your preservation needs. Mix and match the right combination of product attributes for optimum performance.

Performance Benefits of ACRYLITE®

Framing Grades	Defect Free	Conservation UV-filtering	Non-glare Matt finish	Abrasion Resistant	Thicknesses	Sheet Sizes*
Extruded						
UV filtering (OP3)	•	•			.098″ .118″ .177″ .236″	48″x 96″ 75″ x 126″ 101″ x 168
Non-glare (P99)	•		•		.060" .080" .098" .118" .177" .236"	48″x 96″ 61″x 97″
UV filtering with 1-side abrasion resistan	t •	•		•	.098″.118″	48″x 96″
UV filtering with non-glare	•	•	•		.090″ .118″	48″x 96″
Framing grade (FF3)	•				.060" .080" .090" .098" .118" .177" .220"	48″x 96″ 72″ x 96″
Cast						
UV filtering (OP2)	•	•			.118" .177" .236" .354" .472"	51″ x 100″ 75″ x 100″ 80″ x 120″



The Perfect Complement for finishing & maintaining ACRYLITE*!

ACRIFIX[®] Anti-Static Cleaner

ACRIFIX[®] AC 1010 antistatic cleaner is the product of choice for maintaining ACRYLITE[®] sheet. It polishes to a streak-free shine while removing grease and dust, and its non-toxic formula is environmentally friendly. ACRIFIX[®] AC 1010 cleaner is available in 4 ounce, 16 ounce and gallon bottles.

ACRIFIX® Specialty Bonding Agents

ACRIFIX[®] 2R 0190 Versatile, the quintessential reactive SBA, is viscous, dries clear and bubble-free making it ideal for shadowboxes and vitrines where archival integrity is paramount.

Evonik Cyro LLC | ACRYLITE® Conservation Glazing | 3719D-0114-cyro Page 2/2

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Industries is a worldwide manufacturer of PMMA products sold under the ACRYLITE* trademark in the Americas and under the PLEXIGLAS* trademark in the European, Asian, African and Australian continents. Windex* is a registered trademark of the SC Johnson Company. ©2012 Evonik Cyro LLC. All rights reserved. Printed in USA.

Evonik Cyro LLC 299 Jefferson Road, Parsippany, NJ 07054 US PHONE +1 800 631-5384 www.acrylite.net www.acrylite-shop.com

